

# 12 Volt DC Standard Pump Line Designed for 2" and Larger Diameter Wells

## PROACTIVE ENVIRONMENTAL PRODUCTS®



### 12 Volt Typhoon® Plastic Pump (Lifts 50 Feet / 15 Meters DTW)

#### Specifications

- 길이/직경: Length 30.48cm / Diameter: 4.62cm
- 튜빙사이즈: 3/8Inch or 1/2Inch ID tubing
- 깊이: 15m DTW
- 배터리: 12V battery
- 사용되는 컨트롤러: Low Flow Sampling Controller

#### Performance

펌프 깊이(m)	토출량(L/min)
0.9	11.4
3.1	8.7
6.1	7.6
7.6	5.7
9.1	3.8
12.2	2.3
15.2	1
16.8	-



### 12 Volt Tornado® Plastic Pump (Lifts 100 Feet / 31 Meters DTW)

#### Specifications

- 길이/직경: Length 68.58cm / Diameter: 4.62cm
- 튜빙사이즈: 3/8Inch or 1/2Inch ID tubing
- 깊이: 31m DTW
- 배터리: 12V battery
- 사용되는 컨트롤러: Low Flow Sampling Controller

#### Performance

펌프 깊이(m)	토출량(L/min)
0.9	14.2
3.1	13.2
6.1	11.4
9.1	10.4
12.2	9.5
15.2	7.6
18.2	5.7
21.3	3.8
24.4	1.9
27.4	1.5
30.5	1



### Low Flow Sampling Controller

#### Features

- 40mL/min 까지의 저유량 컨트롤러
- 12V 전원 사용
- 중량 강화 플라스틱 방수 케이스
- 내장된 차단기
- Ramp Up 조절 다이얼